

GinkGo 2023 Original Specification

Frame set	See further below for specifications
Group set	Shimano XT throughout 1x11 drivetrain Front brake 160 mm disc Rear brake 180 mm disc Narrow-wide 34T chainring Hollowtech II crankset
Wheels	700c / 622 mm or 27,5" / 584 mm Thru axle (see frame) 32 hole rims, double walled Stainless steel spokes with brass nipples Sturdy urban tires Tubes with Presta valves
Fork	Carbon fork with tapered steerer (comes in black only) 15 x 100 mm thru axle PM attachment for disc brake. For 160 mm disc (larger disc sizes with adapter) Max tire width with mud guards is 47 mm or 2.1" with 27.5" wheels
Also included	Black aluminium alloy seat post Saddle Mud guards Black flat aluminium alloy handlebar Comfortable grips Platform pedals

Accessories

Child seats	Single or double child seat
Panels	Custom print available upon request
Spare parts	All parts included with the frame set are available as spares

Frame set

Frame	GinkGo 6061 T6 heat treated aluminum alloy Powder coated in RAL color of your choice, our standard Traffic Red - 3020, or RAW 30.9 mm seat post diameter (for 36.6 mm seat post clamp, included) BSA 73 mm BB shell Tapered headtube 12 x 142 mm thru axle Up to 180 mm disc rotor With 622 mm (28") road wheels the max tire width is 47 mm and with 27.5" MTB wheels the maximum tire width is 2.1"
Kick stand	Black anodized aluminum alloy kick stand with replaceable feet A taller suspension fork version is separately available
Steering	Black anodized aluminum rod, links and and stainless steel fasteners
Max capacity	180 kg including rider: max 70 kg on cargo deck and max 25 kg on rear rack (Rear rack needs to be purchased separately)