

GinkGo 2023 Electric Specification

| | |
|---------------|--|
| Frame | GinkGo 6061 T6 heat treated aluminum alloy Powder coated in RAL color of your choice, our standard Traffic Red - 3020, or RAW 30.9 mm seat post diameter (for 36.6 mm seat post clamp, included) Tapered headtube 12 x 142 mm thru axle Up to 180 mm disc rotor With 622 mm (28") road wheels the max tire width is 50 mm and with 27.5" MTB wheels the maximum tire width is 2.25" |
| Drive | Brose S ALU drive Torque 90 Nm Maximum assistance 380% Assistance up to 25 km/h Continuous rated power 250W Walk assist 36 Volt, 11 Ah, 396Wh Battery. Option: 17.5Ah, 630 Wh |
| Group set | Shimano XT throughout 1x11 drivetrain Front brake 160 mm disc Rear brake 180 mm disc Narrow-wide 34T chainring Hollowtech II crankset |
| Wheels | 700c / 622 mm or 27,5" / 584 mm Thru axle (see frame and fork) 32 hole rims, double walled Stainless steel spokes with brass nipples Sturdy urban tires Tubes with Presta valves |
| Kick stand | Black anodized aluminum alloy kick stand with replaceable feet |
| Steering | Black anodized aluminum rod, links and and stainless steel fasteners |
| Fork | Carbon fork with tapered steerer (comes in black only) 15 x 100 mm thru axle PM attachment for disc brake. For 160 mm disc Max tire width with mud guards is 50 mm or 2.25" with 27.5" wheels |
| Also included | Black aluminum alloy seat post Saddle Mud guards Black flat aluminum alloy handlebar Comfortable grips Platform pedals |
| Max capacity | 180 kg including rider: max 70 kg on cargo deck and max 25 kg on rear rack (Rear rack needs to be purchased separately) |